


Remote Chime, Model SC546A

INSTALLATION AND OPERATING INSTRUCTIONS

1. Set the Housecode dial on the SC546A to the same letter as your X10 Controller (TM751, MS13A, MC460, etc).
2. Set the Unit Code dial on the SC546A to any unused number between 1 & 16. If you are using it with a HawkEye Motion Detector, set it to the same Housecode and Unit Code as the HawkEye (MS13A/MS14A) and Transceiver (TM751).
3. Plug the SC546A into any unused AC outlet (not one that is controlled by a wall switch, in case the switch accidentally gets turned off).
4. To test the SC546A, press the number button (on any X10 Controller) corresponding to the Unit Code you set on the SC546A. Or walk past a HawkEye Motion Detector. The HawkEye sends a signal to the TM751 which retransmits it over your house wiring to the SC546A. The SC546A then chimes.



Check Out our Web site at:

www.x10.com

For more information on X10 products and special promotional offers.

X10 (USA) INC. LIMITED 1-YEAR WARRANTY

X10 (USA) Inc. warrants X10 products to be free from defective material and workmanship for a period of one (1) year from the original date of purchase at retail. X10 (USA) Inc. agrees to repair or replace, at its sole discretion, a defective X10 product if returned to X10 (USA) Inc. within the warranty period and with proof of purchase.

If service is required under this warranty:

1. Return the defective unit postage prepaid to X10 (USA) Inc. (see address on back).
 2. Enclose a check for \$4.00 to cover postage and handling.
 3. Enclose a dated proof of purchase.
 4. X10 is not responsible for shipping damage.
 5. Units to be returned should be packed carefully.
- For additional warranty information, contact X10 (USA) Inc.

Your Name

Address

Date Purchased 19 .. Store where purchased

SC546A-0799

FROM
X10 (USA) Inc.
91 Ruckman Rd., Box 420, Closter, NJ 07624-0420

First Name	Last Name	
<input type="text"/>	<input type="text"/>	
Street Address - No P.O. Box numbers (for U.P.S.)		
<input type="text"/>		
City	State	Zip
<input type="text"/>	<input type="text"/>	<input type="text"/>

CONTENTS - MERCHANDISE RETURN POSTAGE GUARANTEED
POSTMASTER THIS PARCEL MAY BE OPENED FOR POSTAL INSPECTION

X10 (USA) Inc.
91 Ruckman Rd., Box 420,
Closter, NJ 07624-0420

Mini Timer MT522/MT10A

A Controller, Timer and Alarm Clock all in one! Programs up to 4 modules to go on and off at specific times, twice a day. Controls 8 modules instantly. Dims lights too.

Maxi Controller SC503

Lets you control up to 16 X10 Modules at the touch of a button from anywhere in the house. Dims lights too!

Mini Controller MC460

Lets you control up to 8 X10 Modules at the touch of a button from anywhere in the house. Dims lights too!

2-Way Home Control Interface CM11A

Set up from an IBM compatible PC to control up to 256 X10 Modules. ActiveHome software & cable included.

Thermostat Set-Back TH2807

Automatically sets-back your central heating/air conditioning. Mounts on the wall under your existing thermostat and plugs into an Appliance Module.

Telephone Responder TR16A

Lets you control up to 16 lights and appliances from any outside touch-tone phone.

Wireless Remote Control System RC5000

Lets you control 16 X10 modules from inside or outside your home. Can also dim and brighten Lamp Modules and Wall Switch Modules. Works with the HR12A PalmPad Remote and X10 RF Wall Switches (SS13A, SS15A).

Lamp Module LM465

Can be Dimmed and Brightened from any X10 Controller. Responds to "All lights on". Rated for 300W Incandescent only. 2-Way version LM14A.

Appliance Module - AM486/AM466

Two pin polarized (AM486) or 3 pin grounded (AM466) For controlling an air conditioner, TV, stereo, etc anywhere in the home. Rated 15A for heaters, coffee pots etc.; 1/3 H.P. for motors. 400W for TVs, 500W for lamps. 2-Way versions available AM14A (2 pin), AM15A (3 pin)

Wall Switch Module WS467

For controlling important indoor and outdoor security lights. Replaces your existing wall switch and installs like a regular dimmer. Dimmed/brightened from any X10 Controller. Rated 500W incandescent only

3 - Way Wall Switch Module WS4777

For controlling a light which is controlled by two switches. Same features as WS467.

Split Receptacle Module SR227

Replaces existing wall outlet. The top outlet functions like an Appliance Module, the bottom one is a regular outlet. Rated 15A. Controls ANYTHING which normally plugs into a regular AC outlet.

Universal Module UM506

Isolated contact relay and beeper. Can be set for momentary or continuous operation. Not compatible with DS7000 and DC8700 security systems.